

PRESTIJ LUX SYNTHETIC LAST LAYER PAINT



Application Recommendations

Application Areas

- Can be used safely with appropriate undercoat on wood, iron-steel, cement, concrete, plaster, cement board, gypsum board, OSB, MDF interior and exterior surfaces.

Equipment



Synthetic Anticorrosion



Synthetic Undercoat



Gold Lux Last Layer Paint

Equipment



Scrapper



Gypsum trowel



Putty shovel



Spatula



Trowel



Dust Cloth



Brush



Mixer



Adjustable Stick



Paint Bucket

Surface Preparation



Mortar



Concrete



Cement Board



Gypsum Panels



Old Plastic Paint



Plaster Board




Glasstextile



Wallpaper

- Surface must be removed from oil, dirt, rust and blistered paint.
- Should be made sanders before application, surfaces must be cleaned and priming with Gold synthetic Undercoat. Old Painted and metal surface must be free from rust with sandpaper. If not signs of rust surface should be priming with synthetic undercoat and should then be painted with Gold Lux Synthetic Topcoat after correction surface with fine sandpaper.
- New wood surfaces to be painted surfaces must be primed with Gold Synthetic Undercoat after saturating the wood preservative. Should be applied twice Gold Antirust new painted and iron-steel surfaces.
- Gold Lux Synthetic Topcoat by brush, roller, or spray application to bring consistency must be thoroughly mixed with the synthetic thinner thinned 5-10%.
- Gold Lux Synthetic Topcoat applied sanded prepared surfaces after 24 hours by brush, roller, or spray gun. Must be waited 1 day between layer application.
- Airless spray pressure of 120-140 bar, nozzle angle 50 °, size should be 0.013 inches.
- Application tools should be cleaned with thinner immediately after use.
- Temperature should be between 5 ° C-30 ° C during the application.

Application



During application and during the subsequent 24 hours at the ambient temperature of the surface should be +5 ° C.



Before application Nano Clean Interior Paint should be mixed.



Nano Clean Interior Paint thinned with clean water 10% and application for two layer by brush, roller or spray.



Should be waited minimum 6 hours between layers.

After Application

Application tools should be washed with water after use immediately.

PRESTIJ LUX SYNTHETIC LAST LAYER PAINT



Exterior

Interior

Water

Product Code: 242

Product Description

- ◆ It is Luxury Bright Topcoat Paint with alkyd resin based and lead-free.

Application Areas

- ◆ Can be used safely with appropriate undercoat with on wood, iron-steel, cement, concrete, plaster, cement board, gypsum board, OSB, MDF interior and exterior surfaces.

Advantages

- ◆ It has superior cover power.
- ◆ High and lasting shine.
- ◆ Excellent cleanable and has adhesion to a substrate.



Matt



Brush



Roll



Spray Pistolet

Technical specifications:

Structure

- ◆ Alkyd resin based, Solvent based

Diluting

- ◆ Water

Appearance on the packing

- ◆ Dark, Stable, Jelly

Dry Appearance

- ◆ Bright, Smooth.

Color

- ◆ White and 32 colors in the colour chart

Water Vapor permeability

- ◆ SD (m) (TS EN ISO 7783-2):
Approximately: 50

Drying Time

- ◆ (between +5 +35 °C)
Touching time: 3 hours Doesn't hold dust for 8 hours. Complete drying time: 24 hours. Lower temperature or high relative humidity lengthens the drying time.

Coverage

- ◆ Depending on the surface smoothness and absorbency approximately 14,5-17 m²/lt. per a layer.

Shelf Life

- ◆ In package and in 5-35 °C 2 years

Packing

- ◆ 20 - 10 - 3 kg tin bucket.

Safety Recommendations

- ◆ S2: Keep out the reach of children.
- ◆ S24/25: Avoid contact with eyes and skin.
- ◆ S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- ◆ S28: In case of contact with skin immediately wash with water.
- ◆ S29: Do not discharge into drains or water courses.
- ◆ S46: If swallowed, seek medical advice immediately and show the container or label.
- ◆ Mix before using. Close the cover after using.
- ◆ Protect from frost and direct sunlight.

Quality Certificate

- ◆  TS 39

Public exposure No: 04.524/6 04.506/E3

