

GOLD EXTERIOR PASTE



Exterior

Water

Application Recommendations

Application Areas

- In exterior, can be used on the surfaces such as in accordance mortar, concrete, cement, boards, gypsum panel.

Equipment



Fillers



Gypsum Undercoat



Acrylic Putty



Acrylic Paste

Equipment



Scraper



Gypsum trowel



Puttyshovel




Spatula



Trowel



Dust Cloth



Brush



Mixer



Adjustable Stick



Paint Bucket



Sprayer

Surface Preparation



Mortar



Concrete



Cement Board



Gypsum Panels



Old Plastic Paint



Plaster Board



Glasstextile



Wallpaper

- Gold Exterior Paste applicable cleaned every dirt, oil, dry and solid of the swollen layers. Can obtain maximum benefit from the Gold Exterior Paste, must be removed from accordance mortar, raw concrete, cement gypsum board and made ceiling paint, dirt, dust and adhesion surfaces. Should be cleaned worm, swollen, completely perforated plate of paints.

- Unless there is a purpose to the new paint coarse grained mortar, concrete, surface must be smoothed with fillers such as cement board.

- If necessary, the surface cracks should be filled with acrylic putty, defects to be remedied.

- The best way to ensure the entire surface is shiny satiny touch will be applied after smoothing Gold Interior paint and primer will reduce consumption to ensure good adhesion of the paint as well.

- The best way to ensure the entire surface is shiny satiny touch will be applied after smoothing Gold Interior paint and primer will reduce consumption to ensure good adhesion of the paint as well.

- Old painted moldy surfaces before application on the surface should be cleaned with damp cloth. Thoroughly with emery paper, the surface must be removed. If soot and mold drying preemptive 2-3 coats should be applied.

Application



During application and during the subsequent 24 hours at the ambient temperature of the surface should be +5 ° C.



Before application Gold Exterior Paste should be mixed.



Gold Exterior Paste thinned with clean water 10% and application for two layer by brush, roller or spray.



Should be waited minimum 6 hours between layers.

After Application

Application tools should be washed with water after use immediately.

GOLD EXTERIOR PASTE



Exterior

Water

Product Description

- ◆ It is acrylic emulsion based smoothing paste that is used as the section on the exterior surface at an optimum thickness to eliminate surface defects.

Application Areas

- ◆ Is used as coating material for smoothing of rough concrete and mineral surfaces, the filling of shrinkage cracks and the elimination of surface defects due to removal of old paint blistered

Advantages

- ◆ Very durable, non-dusting and create a smooth surface.
- ◆ Resistant to moisture.
- ◆ Does not prevent the walls of the breathing.
- ◆ Absorbency is lower because of absorbency is lower.
- ◆ The application is very easy.
- ◆ Fill power is very high, which makes at most 2 times the surface smooth.
- ◆ Not much dust during sanding.
- ◆ Does not harm health of environment and not smell because solvent free.



Matt



Brush



Roll



Spray Pistle

Technical specifications:

Structure

- ◆ Acrylic emulsion based, water based

Diluting

- ◆ Water

Appearance on the packing

- ◆ Dark, Stable, Jelly

Dry Appearance

- ◆ Matt, Pastel, Smooth

Color

- ◆ Bone Colour

Water Vapor permeability

- ◆ SD (m) (TS EN ISO 7783-2): Approximately: 180

Drying Time

- ◆ (between +5 +35 °C) complete drying time is 24 hours. Ossification time is one week. Lower temperature or high relative humidity lengthens the drying time.

Coverage

- ◆ Depending on the surface smoothness and absorbency also application thickness approximately 3-4 m²/lt.

Shelf Life

- ◆ In package and in 5-35 °C 2 years

Packing

- ◆ Net 25 kg plastic bucket.

Safety Recommendations

- ◆ S2: Keep out the reach of children.
- ◆ S24/25: Avoid contact with eyes and skin.
- ◆ S26: In case of contact with eyes immediately wash with water and contact with a doctor.
- ◆ S28: In case of contact with skin immediately wash with water.
- ◆ S29: Do not discharge into drains or water courses.
- ◆ S46: If swallowed, seek medical advice immediately and show the container or label. Mix before using. Close the cover after using. Protect from frost and direct sunlight.



Quality Certificate

- ◆ TSE K 276
Public exposure No. 04.524/604.506/E3